

Crystalyte G Series

Rear Motor 40KM Max Speed

Description	U	I	P1	M	N	P2	Eff
	(V)	(A)	(W)	(N.m)	(rpm)	(W)	(%)
Unload	36.00	1.116	40.19	0.00	355.7	0.00	0.0
Max-Eff	35.71	7.850	280.3	7.06	295.6	218.5	77.9
Max-Pout	35.09	21.69	761.5	21.73	198.3	451.1	59.2
Max-Torque	35.01	25.67	899.1	31.57	57.1	188.7	20.9
End	35.01	25.67	899.1	31.57	57.1	188.7	20.9

NO:	U	I	P1	M	N	P2	Eff
	(V)	(A)	(W)	(N.m)	(rpm)	(W)	(%)
1	36.00	1.116	40.19	0.00	355.7	0.00	0.0
2	35.98	1.437	51.73	0.34	352.7	12.55	24.2
3	35.97	1.865	67.09	0.78	349.2	28.51	42.5
4	35.95	2.488	89.47	1.41	343.6	50.72	56.6
5	35.91	3.354	120.4	2.20	334.9	77.14	64.0
6	35.86	4.353	156.1	3.23	326.3	110.3	70.6
7	35.81	5.446	195.0	4.38	317.4	145.5	74.6
8	35.76	6.637	237.3	5.64	306.6	181.0	76.2
9	35.71	7.850	280.3	7.06	295.6	218.5	77.9
10	35.64	9.285	330.9	8.53	285.2	254.7	76.9
11	35.58	10.74	382.4	10.06	274.0	288.5	75.4
12	35.45	12.18	432.0	11.70	262.0	320.9	74.2
13	35.39	13.67	484.1	13.32	251.2	350.3	72.3
14	35.32	15.33	541.6	14.96	240.8	377.1	69.6
15	35.27	16.87	595.2	16.70	229.9	401.9	67.5
16	35.24	18.47	651.0	18.44	218.6	422.0	64.8
17	35.17	20.12	707.8	20.08	208.4	438.1	61.9
18	35.09	21.69	761.5	21.73	198.3	451.1	59.2
19	35.05	23.20	813.4	23.54	180.5	444.8	54.6
20	35.07	23.68	830.6	25.30	154.1	408.1	49.1
21	35.05	24.11	845.5	26.91	129.5	364.8	43.1
22	35.02	24.82	869.6	28.46	109.7	326.8	37.5
23	35.00	25.50	892.8	30.08	80.0	251.9	28.2
24	35.01	25.67	899.1	31.57	57.1	188.7	20.9