

Crystalyte-NSM25 15A36V

Descripton	U	I	P1	M	N	P2	Eff
	(V)	(A)	(W)	(N.m)	(rpm)	(W)	(%)
Unload	36.74	0.537	19.76	0.01	363.5	0.38	1.9
Max-Eff	36.47	4.956	180.7	4.34	297.5	135.1	74.7
Max-Pout	35.76	14.43	516.2	12.94	181.9	246.4	47.7
Max-Torque	35.66	17.16	612.1	16.22	99.2	168.4	27.5
End	35.66	17.16	612.1	16.22	99.2	168.4	27.5

NO:	U	I	P1	M	N	P2	Eff
	(V)	(A)	(W)	(N.m)	(rpm)	(W)	(%)
1	36.74	0.537	19.76	0.01	363.5	0.38	1.9
2	36.73	0.640	23.54	0.08	362.0	3.03	12.8
3	36.72	0.942	34.60	0.38	357.3	14.21	41.0
4	36.69	1.408	51.68	0.83	348.8	30.31	58.6
5	36.66	2.056	75.38	1.46	339.6	51.91	68.8
6	36.62	2.873	105.2	2.25	328.0	77.26	73.4
7	36.56	3.839	140.4	3.19	313.6	104.7	74.5
8	36.47	4.956	180.7	4.34	297.5	135.1	74.7
9	36.13	6.258	226.1	5.56	278.2	161.9	71.6
10	36.07	7.574	273.2	6.93	260.8	189.2	69.2
11	36.06	9.088	327.7	8.31	243.3	211.6	64.5
12	36.02	10.69	385.4	9.82	223.8	230.1	59.6
13	35.96	12.51	450.1	11.34	204.7	243.0	53.9
14	35.76	14.43	516.2	12.94	181.9	246.4	47.7
15	35.71	16.52	590.3	14.54	158.0	240.5	40.7
16	35.66	17.16	612.1	16.22	99.2	168.4	27.5